

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : C07C 211/63, G01N 31/22, A61M 16/04		A1	(11) International Publication Number: WO 00/02844
			(43) International Publication Date: 20 January 2000 (20.01.00)
(21) International Application Number: PCT/GB99/02081 (22) International Filing Date: 12 July 1999 (12.07.99) (30) Priority Data: 9815001.4 11 July 1998 (11.07.98) GB (71) Applicant (for all designated States except US): SEN- SORMETRIX INTERNATIONAL LIMITED [---]; Caribbean Corporate Services Limited, Omar Hodge Building, Wickhams Clay 1, P.O. Box 362, Road Town, Tortola (VG). (72) Inventors; and (75) Inventors/Applicants (for US only): ALBADRAN, Ja- far [IQ/GB]; City Technology Limited, Walton Road, Portsmouth PO6 1SZ (GB). McMURRAY, Neil, Hamilton [GB/GB]; Department of Materials Engineering, University of Wales Swansea, Singleton Park, Swansea SA2 8PP (GB). (74) Agent: GILHOLM, Steve; Harrison Goddard Foote, Belmont House, 20 Wood Lane, Leeds LS6 2AE (GB).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report.	
(54) Title: QUATERNARY AMMONIUM SALTS, POLYMERIC FILM CONTAINING THEM AND COLORIMETRIC DEVICE <div style="text-align: center;"> $\begin{array}{ccc} R_1 & & R_3 \\ & & \\ -(CH_2)_n-N^+- & - & -(CH_2)_m-N^+- \\ & & \\ R_2 & & R_4 \end{array} \quad (I)$ </div>			
(57) Abstract There is described a polymeric quaternary alkyl ammonium cation of general formula (I), or a salt thereof; in which R ₁ , R ₂ , R ₃ and R ₄ , which may be the same or different are each alkyl C1 to 20; m is an integer from 1 to 100; and n is an integer from 1 to 7. There is also described a film formulation comprising a cation of formula (I), a colorimetric sensor device comprising said film and an endotracheal intubation apparatus comprising a sensor.			

BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CJ	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

QUATERNARY AMMONIUM SALTS, POLYMERIC FILM CONTAINING THEM AND COLORIMETRIC DEVICE

This invention relates to oligomeric/polymeric quaternary alkyl ammonium cations, and salts thereof, for incorporation in colorimetric film sensors particularly for the
5 detection of carbon dioxide.

Carbon dioxide sensors are known which incorporate quaternary alkyl ammonium salts of pH indicator dye acids and carbonic acid within a thin transparent polymer membrane. They act as rapidly responding, reversible and non-consuming
10 detectors of carbon dioxide in the gas phase. Such sensors respond by changing colour on exposure to carbon dioxide. Furthermore, the response may be made quantitative by monitoring optical absorbance e.g. using monochromatic light. Colour change occurs through the reversible protonation of the indicator dye anion by carbonic acid formed by the reversible reaction of carbon dioxide with water
15 bound within the film. Such sensor films have applications in medicine, horticulture, air conditioning systems, environmental monitoring and industrial health and safety.

The use of such quaternary alkyl ammonium salts is described in, *inter alia*, US Patent No. 5,005,572, European Patent No. EP 0 509 998 and International Patent
20 Application No. WO 96/24054.


Known quaternary alkyl ammonium cations, and their salts, tend to be mobile within a sensor film and can therefore be lost through migration. Migration places
significant restriction on the choice of sensor substrate (which must be compatible
25 with the quaternary alkyl ammonium salt).

Also, known quaternary alkyl ammonium salts are not universally compatible with organic polymers, further restricting the choice of polymers for sensor film
formulation.

30

We have now surprisingly found that a high molecular weight oligomeric/polymeric quaternary alkyl ammonium cation, or salts thereof, which are less mobile within a sensor film reducing the extent to which migration can occur. Reduced migration allows a wider choice of substrate materials which may now be thermodynamically compatible with the quaternary ammonium salt.

According to the invention we provide a polymeric quaternary alkyl ammonium cations of the general formula I and salts thereof.



in which R₁, R₂, R₃ and R₄, which may be the same or different, are each alkyl C1 to C20;

m is an integer from 1 to 100; and

n is an integer from 1 to 7.

By the term polymeric, it is also intended to include oligomeric.

R₁, R₂, R₃ and R₄, which may be the same or different, are preferably alkyl C5 to 10.

It is preferred that the values of n and m together should have a total in the range of from 4 to 8.

Preferably, m is an integer from 1 to 50, more preferably from 1 to 25, especially 1 to 10 and particularly 1 to 7.

Particularly preferred salts are 1,8-octane-di-tripentyl ammonium bromide and 1,8-octane-di-tripentyl ammonium hydroxide.

The salts of the cations of formula I may be selected from the group halide e.g. fluoride, chloride, bromide or iodide; hydroxide; carbonate and tetrafluoroborate. Of the halides, bromide salts are preferred, but especially preferred are the hydroxide salts.

5

These provide increased migration/leaching resistance for the quaternary alkyl ammonium pH indicator dye salts and bicarbonate salts essential for sensor function.

The cations of formula I, and thereof, are advantageous in that they produce an improved pH indicator dye with a greater compatibility with polymers, therefore allowing a wider choice of polymers for sensor film formulation.

10

According to a further feature of the invention we provide a film formulation comprising a cation of formula I, or a salt thereof, in intimate mixture with a transparent film-forming polymer vehicle.

15

The transparent film-forming polymer vehicle should be compatible with the indicator material, such that the latter does not exude or otherwise undergo phase separation over a prolonged period (for the intended lifetime of the sensor). Thus, the film-forming polymer should be volatile, e.g. at room temperature and the polymeric quaternary ammonium cation, or a salt thereof, should be soluble in the polymer. The film-forming polymer vehicle should preferably be hydrolytically stable in order to avoid unwanted changes in the pH in the absence of carbon dioxide. The polymer should furthermore be permeable to carbon dioxide.

20

The hydrolytically stable film-forming polymer may be water-soluble or organic solvent-soluble. It is preferred that the film-forming polymer is organic solvent soluble. Examples of suitable organic solvent soluble film-forming polymers include polyvinyl butyral, polyvinyl methyl ether, polymethyl ether, polymethyl methacrylate, ethyl cellulose and polystyrene.

25

Examples of water-soluble film-forming polymers which also have good resistance to hydrolysis include hydroxypropyl cellulose, methyl cellulose, carboxymethyl cellulose, polyethylene glycol, polyvinyl alcohol (100% hydrolysed) and polypropylene glycol.

5

Further examples of polymers include polydimethyl silicone, and polyurethane.

According to another feature of the invention we provide a colorimetric sensor device containing one or more of the aforementioned quaternary ammonium salts. Such a device may generally comprise;

10

a polymeric quaternary ammonium cation of formula I, or a salt thereof;
at least one pH sensitive dye; and
a film-forming polymer.

15

Any conventionally known pH sensitive dyes may be used, including thymol blue, m-cresol purple, xyleneol blue and/or cresol-red.

20

The volatile polymer or oligomer may be any such material which is conventionally known in the art, for example, such as is described in PCT patent application No. WO96/24054 which describes that the film forming component is preferably a water-insoluble low volatility organic substance, which is not susceptible to alkaline hydrolysis and is liquid at temperatures below 100°C, e.g. at room temperature, or is semi-solid e.g. of waxy structure, at room temperature.

25




Compounds which are "susceptible to alkaline hydrolysis" includes compounds such as those containing ester groups which are subjected to alkaline hydrolysis in the presence of a basic component.

30

The film forming component may have a molecular weight (weight average molecular weight = M_w) below 15,000, preferably below 10,000. The film forming

component may be selected from the group consisting of alcohols, phenols and alkoxyated derivatives of such substances, e.g. having at least one linear or branched polyether. The film forming component may have be a compound having one of the following structures:

5



10

wherein R^9 and R^{12} each represents H or a linear or branched hydrocarbon residue of 1 to 50 carbon atoms, optionally containing one or more double bonds, triple bonds and/or ring structures,

R^{10} , R^{11} and R^{13} each represents a linear or branched hydrocarbon residue of 1 to 10

15 carbon atoms,

x and y are equal or different integers from 0 to 100,

p is an integer from 1 to 6, and

q and r are equal or different integers from 0 to 4.

20 Examples of compounds having the above structures (I) to (IV) are the following:

Polyalkylene glycols, such as polyethylene glycols, polyethylene glycols, polypropylene glycols, polybutylene glycols and copolymers of ethylene oxide, propylene oxide and/or butylene oxide. Other linear polyethers, such as

25 polytetrahydrofurans. Alkoxyated alcohols or phenols, such as ethoxylated, propoxylated or butoxylated alcohols derived from fatty alcohols (straight or branched, saturated or unsaturated, etc), alkyl phenols, dialkyl phenols, alkyl naphthalenes, bisphenol A, alkyne diols, lanolin, cholesterol, phytosterol, sitosterol, glucose ethers and silicones; and mixed ethoxylated/propoxylated alcohols.

30 Branched polyethers, for instance products obtained by ethoxylating and/or propoxylating trimethylol propane or pentaerythritol. Alkoxyated amines, such as

ethoxylated and/or propoxylated primary or secondary amines or diamines. Alkoxyated (ethoxylated and/or propoxylated) thiols. Dialkyl ethers, e.g. dioctyl ether.

- 5 Silicone oligomers or polymers may also be used since they have the advantage that, *inter alia*, they are highly permeable to carbon dioxide. For example, a typical silicone polymer has permeability (that is, the gas transmission rate of a film of the polymer of thickness 0.001 inch, expressed as cubic centimetres of gas transmitted through 1 mm of film per 24 hours per square inch of film with one atmosphere differential across the film) is typically as follows:

15 About 100,000 for oxygen and about 500,000 for carbon dioxide (compared with figures of respectively about 1,000 and 5,000 for PTFE; 500 and 2,000 for low density polyethylene; 100 and 500 for cellulose acetate; and 1 and 1 for polyvinylidene chloride).

20 The silicone oligomers and polymers are, easy to handle and to apply to a suitable substrate using an organic solvent such as a hydrocarbon type solvent (such as hexane), a chlorinated solvent (for example, chloroform or dichloromethane), an ether solvent (such as tetrahydrofuran), or a low molecular weight oligomeric silicone (such as a cyclic dimethyl silicone).

25 Because the silicone oligomers or polymers are substantially non-curable they have good storage stability and can be stored indefinitely in the solvent.

30 The silicone oligomers or polymers are also readily compatible with the pH sensitive dye and the basic substance, and can be applied in the form of a film on a preformed substrate (such as a plastics, paper or glass substrate). Alternatively, the silicone may be applied as an impregnation throughout a porous carrier medium, for example, of glass fibre, paper, plastics, textile fabric or the like. It is particularly preferred to use

such materials which have been provided with a hydrophobic surface treatment, for example, by silanisation.

The silicone oligomers or polymers are preferably substantially linear and
5 substantially free of hydrophilic groups; preferred substituents for the silicone chain are methyl groups (although other low molecular weight hydrophobic groups may be employed, such as ethyl or trifluoromethyl groups).

It is particularly preferred that the silicone oligomer or polymer is a linear
10 polydimethylsiloxane. The silicone preferably has a molecular weight in the range of 200 to 200000, and is preferably optically transparent. When higher molecular weight silicone polymers are used they are very good binders and have a low glass transition temperature such that they maintain their physical properties over a wide range of temperatures. They are furthermore non-toxic and non-volatile, and
15 hydrolytically stable.

The silicone oligomers or polymers are furthermore compatible with the indicator ingredients (the dye and the basic substrate), and can be free of migratable low molecular weight materials such as plasticisers or the like.

20

Preferably the device will be in the form of film sensor and the film may therefore require a support such as a polypropylene proper sheet, a cellulose layer or a plastics foil material. However, the sensor of the invention preferably comprises a silanised
25 paper support which is preferably non-translucent i.e. is reflective, such as a white film which aids in visual indication. Alternatively the support may be a transparent film on a glass substrate which permits quantitative interrogation with e.g. monochromatic light.

30 The sensor device of the invention functions by the reaction of carbon dioxide with traces of water bound within the sensor film to form carbonic acid (H_2CO_3). Thus,

dissociation of H_2CO_3 to H^+ and HCO_3^- produces a fall in sensor pH which in turn produces an optical absorbance change through the reversible protonation of the pH indicator dye.

- 5 Thus, according to a further feature of the invention we provide a method of carbon dioxide detection which comprises placing a sensor according to the invention *in situ* and observing a colour change.

The sensors of the invention have particular utility in determining the proper
10 placement of a tracheal tube of an endotracheal intubation device in a patient.

Thus, a further feature of the invention is to provide an endotracheal apparatus comprising a sensor as hereinbefore described.

- 15 We further provide a method for determining the proper placement of an endotracheal tube which comprises inserting an endotracheal tube comprising a sensor according to the invention, into a patient and observing a colour change.

The invention will now be described, but in no way limited by the following
20 examples.

Example 1

Preparation of 1,8 Octane-di-tripentyl Ammonium Bromide


25

Chemicals

- Tri Pentyl Amine (TPA) 97%, fw: 227.44, bP: 81-83°C, d: 0.788.
- 1,8-Dibromooctane (DBO) 98%, fw: 286.06, bp: 270-272°C, d: 1.477.
- 30 • Methanol, d: 0.791.


Experimental and Results

The reactants DBO and TPA were mixed in a 1:2 molar ratio plus an excess of 50% of TPA. Thus, 5g of DBO, 13g of TPA and 18g of methanol were refluxed together at 68°C for 64 hours. Methanol and excess amine were removed under vacuum at 70°C using a rotary evaporator. The result was a biphasic liquid which rapidly separated into two layers. The top layer was a colourless liquid (code name DC-2L0 which can easily be poured off from the bottom thick oily layer (code name DC-2S were examined by mass spectrometry. The results obtained using electro-spray mass spectroscopy showed that DC-2S contained the target molecule octane-1,8-di-tripentyl ammonium bromide formed through the reaction:



15 R is C_5H_{11} R' is C_8H_{16}

The new doubly charged dimeric tetraalkyl ammonium salt Octane-1,8-di-tripentyl Ammonium Bromide (OTAB) has a formula weight of 726.91. The chemical structure of OTAB is shown below:



25

1,8-Octane-di-Tripentyl Ammonium Bromide (OTAB)

C₃₈H₈₂NBr₂, f.w: 726.91

5 Example 2

Carbon dioxide Film Sensor using OTAB

3.63g of OTAB was dissolved in 12g (15.2mL) of methanol. 4g of Ag₂O was added
10 to the solution and stirred for four hours. The resulting 20% w/w methanolic
solution of the hydroxide salt 1,8-Octane-di-tripentyl ammonium hydroxide
(OTAOH) was collected by decantation.

0.1g of the pH indicator dye (m-cresol purple, thymol blue or xlenol blue) was
15 dissolved in 10g of the 20% w/w OTAOH methanolic solution. Methanol was
evaporated using a rotary evaporator and 7.9g of tetrahydrofuran was added to form a
20:1% base:dye solution.

0.3g of the base:dye solution was added to 10g of 3% w/w polydimethyl silicone
20 (PDMS) polymer solution and mixed before applying to a IPS filter paper.

Filter papers loaded with the sensor materials above showed a good response to 5%
carbon dioxide and it is limited by the pH operating range of the dye. Adding a small
amount (0.5-20 parts per hundred parts polydimethyl silicone) of polyethylene glycol
25 (PEG) was again found to increase both the equilibrated sensitivity to CO₂ and the
sensor response rate.

Samples with the above formulation were prepared with a loading of 20 phr of
OTAOH, 1 phr of m-cresol purple and 2 drops of PEG (~18 phr).

30

Example 3

Film behaviour under Long Term Exposure to Carbon dioxide

- 5 A fresh base:dye solution has been prepared using the conventional "two pot" formulation. 01g of m-cresol purple pH indicator dye was dissolved in 10g of 10% w/w methanolic solution of tetraoctyl ammonium hydroxide (TOAOH). The methanol was replaced by tetrahydrofuran by evaporating the methanol and adding 8.9g of tetrahydrofuran 0.36g of the above base:dye solution was added to 10g of
- 10 10% w/w polymer solution (PDMS in dichloromethane) along with 0.36g of 0.5% w/w PEG before casting on microscope glass slide.

- The film was stored in an airtight glass jar with PURAFIL 100% carbon dioxide was passed into the jar to transform the film to the acidic state (yellow). The film was
- 15 flushed with air after 24, 48, 96 and 800 hours and found to change colour to blue. The above result proved that exposing the film sensor to 100% carbon dioxide does not destroy the film mechanism provided that the film is well protected from other acid gases.

20 Example 4

The Film Shelf Life Test


- Two film sensors were prepared in a similar fashion to the one described in the
- 25 previous example. One of the above films was prepared without the addition of PEG. Both films were stored in an airtight glass jar with some PURAFIL for eighteen months. The films did not show any colour change.

30

CLAIMS

1. A polymeric quaternary alkyl ammonium cation of the general formula I, or a salt thereof;

5



in which R₁, R₂, R₃ and R₄, which may be the same or different, are each alkyl C1 to C20;

10 m is an integer from 1 to 100; and

n is an integer from 1 to 7.

2. A polymeric quaternary alkyl ammonium cation according to Claim 1 characterised in that R₁, R₂, R₃ and R₄, which may be the same or different, are each
15 alkyl C5 to 10.

3. A polymeric quaternary alkyl ammonium salt according to Claim 1 characterised in that the anions of the salts are selected from the group halide, hydroxide, carbonate and tetrafluoroborate.

20

4. A polymeric quaternary alkyl ammonium salt according to Claim 3 characterised in that the halide is selected from fluoride, chloride, bromide or iodide.

5. A polymeric quaternary alkyl ammonium salt according to Claim 4
25 characterised in that the halide is bromide.

6. A polymeric quaternary alkyl ammonium salt according to Claim 3 characterised in that the anion is hydroxide.

7. A polymeric quaternary alkyl ammonium salt according to Claim 5 characterised in that the compound is 1,8-octane-di-tripentyl ammonium bromide.

5 8. A polymeric quaternary alkyl ammonium salt according to Claim 6 characterised in that the compound is 1,8-octane-di-tripentyl ammonium hydroxide.

9. A film formulation comprising a cation, or a salt thereof according to Claim 1, in intimate mixture with a transparent film-forming polymer vehicle.

10

10. A film formulation according to Claim 9 characterised in that the transparent film-forming polymer vehicle is compatible with the indicator material, such that the latter does not exude or otherwise undergo phase separation over a prolonged period.

15 11. A film formulation according to Claim 9 characterised in that the transparent film-forming polymer vehicle is hydrolytically stable.

12. A film formulation according to Claim 9 characterised in that the transparent film-forming polymer vehicle is permeable to carbon dioxide.

20

13. A film formulation according to Claim 9 characterised in that the transparent film-forming polymer vehicle is organic solvent-soluble.

14. A film formulation according to Claim 13 characterised in that the transparent
25 film-forming polymer vehicle is selected from polyvinyl butyral, polyvinyl methyl ether, polymethyl methacrylate, ethyl cellulose and polystyrene.

15. A film formulation according to Claim 9 characterised in that the transparent film-forming polymer vehicle is water soluble.

30

16. A film formulation according to Claim 15 characterised in that the transparent film-forming polymer vehicle is selected from hydroxypropyl cellulose, carboxymethyl cellulose, polyethylene glycol, polyvinyl alcohol (100% hydrolysed) and polypropylene glycol.
- 5 17. A film formulation according to Claim 9 characterised in that the transparent film-forming polymer vehicle is a polyurethane.
18. A film formulation according to Claim 9 characterised in that the transparent
10 film-forming polymer vehicle is a silicone oligomer or polymer.
19. A film formulation according to Claim 18 characterised in that the silicone oligomer or polymer is a polydimethyl silicone
- 15 20. A colorimetric sensor device comprising;
- a polymeric quaternary ammonium cation, or a salt thereof, according to Claim 1
- at least one pH sensitive dye; and
- 20 a polymer in which the polymeric quaternary ammonium cation, or a salt thereof, is soluble.
21. A colorimetric sensor device according to Claim 20 characterised in that the pH sensitive dye is selected from thymol blue, m-cresol purple, xylenol blue and
25 cresol-red.
22. A colorimetric sensor device according to Claim 20 characterised in that the polymer is described in PCT patent application no. WO96/24054.
- 30 23. A colorimetric sensor device according to Claim 20 characterised in that the device is in the form of film sensor and the film is provided with a support.

24. A colorimetric sensor device according to Claim 23 characterised in that the support comprises a material selected from polypropylene sheet, a cellulose layer or a plastics foil material.
- 5 25. A colorimetric sensor device according to Claim 23 characterised in that the support comprises a silanised paper.
26. A colorimetric sensor device according to Claim 23 characterised in that the support comprises a glass substrate.
- 10 27. A method of carbon dioxide detection which comprises placing a sensor according to claim 20 *in situ* and observing a colour change.
- 15 28. An endotracheal intubation apparatus comprising a colorimetric sensor device according to Claim 20.
29. A method for determining the proper placement of an endotracheal tube which comprises inserting an endotracheal tube comprising a colorimetric sensor device according to Claim 20 into the trachea of a patient and observing a colour change.
- 20 30. A colorimetric sensor device substantially as described with reference to the accompanying examples.

25

30

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 99/02081

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 C07C211/63 G01N31/22 A61M16/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C07C G01N A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, X	PATENT ABSTRACTS OF JAPAN vol. 1998, no. 13, 30 November 1998 (1998-11-30) & JP 10 208543 A (TDK CORP), 7 August 1998 (1998-08-07). abstract	1-5, 9-21, 26, 27
X	EP 0 666 277 A (GEN ELECTRIC) 9 August 1995 (1995-08-09) the whole document	1-6
X	DE 22 03 229 A (HUNT CHEM CORP PHILIP A) 26 July 1973 (1973-07-26) claim 1	1, 2
X	DE 19 08 980 A (TH. GOLDSCHMIDT AG) 3 September 1970 (1970-09-03) claim 1	1-5
-/-		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

27 October 1999

Date of mailing of the international search report

04/11/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tr. 31 651 epo nl
Fax: (+31-70) 340-3016

Authorized officer

Rufet, J

INTERNATIONAL SEARCH REPORT

Int'l Application No

PCT/GB 99/02081

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 855 116 C (CIBA AG) 10 November 1952 (1952-11-10) claim 1 ---	1-5
X	DE 905 371 C (MAY & BAKER LIMITED) 1 March 1954 (1954-03-01) page 2 ---	1-5
X	DE 29 05 373 A (GAMBAR LABOR) 6 September 1979 (1979-09-06) claim 1 ---	1-5
X	DE 19 26 436 A (E. R. SQUIBB & SONS INC.) 29 January 1970 (1970-01-29) claims 1-3 ---	1-5
A	WO 96 24054 A (ICOR AB) 8 August 1996 (1996-08-08) cited in the application the whole document ---	1,9-27, 30
A	WO 91 05252 A (ABBEY BIOSYSTEMS LTD) 18 April 1991 (1991-04-18) the whole document & EP 0 509 998 A cited in the application ---	1,9-27, 30
A	WO 89 07957 A (BRIGHAM & WOMENS HOSPITAL) 8 September 1989 (1989-09-08) abstract; claims 1,7-47 & US 5 005 572 A cited in the application ---	1,9-28, 30
A	US 5 426 213 A (IYER LOKANATHAN M ET AL) 20 June 1995 (1995-06-20) the whole document -----	1,9-27, 30

INTERNATIONAL SEARCH REPORT

national application No.

PCT/GB 99/02081

Box I Observations where certain claims were found unsearchable (Continuation of Item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☒ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
Remark: Although claim 29
is directed to a method of treatment of the human/animal
body, the search has been carried out and based on the alleged
effects of the compound/composition.
2. ☒ Claims Nos.: 1-6 partly
because they relate to parts of the International Application that do not comply with the prescribed requirements to such
an extent that no meaningful International Search can be carried out, specifically:
see FURTHER INFORMATION sheet PCT/ISA/210
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of Item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all
searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment
of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report
covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is
restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
☐ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

Continuation of Box I.2

Claims Nos.: 1-6 partly

Present claims 1-6 relate to an extremely large number of possible compounds. Support within the meaning of Article 6 PCT and/or disclosure within the meaning of Article 5 PCT is to be found, however, for only a very small proportion of the compounds claimed. In the present case, the claims so lack support, and the application so lacks disclosure, that a meaningful search over the whole of the claimed scope is impossible. Consequently, the search has been carried out for those parts of the claims which appear to be supported and disclosed, namely those parts relating to the compounds of formula (I) of claim 1 wherein m is an integer from 1 to 7 according to page 2, line 24 of the description. It is stressed that the incomplete search has revealed a very large number of novelty destroying compounds (merely thousand).

The applicant's attention is drawn to the fact that claims, or parts of claims, relating to inventions in respect of which no international search report has been established need not be the subject of an international preliminary examination (Rule 66.1(e) PCT). The applicant is advised that the EPO policy when acting as an International Preliminary Examining Authority is normally not to carry out a preliminary examination on matter which has not been searched. This is the case irrespective of whether or not the claims are amended following receipt of the search report or during any Chapter II procedure.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 99/02081

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
JP 10208543 A	07-08-1998	NONE	
EP 0666277 A	09-08-1995	US 5391692 A CN 1108670 A JP 7252356 A	21-02-1995 20-09-1995 03-10-1995
DE 2203229 A	26-07-1973	NONE	
DE 1908980 A	03-09-1970	AT 300751 B CH 529719 A	15-07-1972 31-10-1972
DE 855116 C		NONE	
DE 905371 C		NONE	
DE 2905373 A	06-09-1979	IT 1094152 B ES 478412 A FR 2418221 A GR 65644 A	26-07-1985 16-01-1980 21-09-1979 15-10-1980
DE 1926436 A	29-01-1970	CH 515881 A FR 2021284 A GB 1277086 A	30-11-1971 17-07-1970 07-06-1972
WO 9624054 A	08-08-1996	SE 504069 C AU 695069 B AU 4357996 A EP 0807250 A JP 10513264 T SE 9500400 A	28-10-1996 06-08-1998 21-08-1996 19-11-1997 15-12-1998 04-08-1996
WO 9105252 A	18-04-1991	DE 69024666 D DE 69024666 T EP 0509998 A US 5472668 A	15-02-1996 22-08-1996 28-10-1992 05-12-1995
WO 8907957 A	08-09-1989	AU 3280289 A US 5005572 A	22-09-1989 09-04-1991
US 5426213 A	20-06-1995	US 5376306 A US 5298645 A AU 3328593 A WO 9313048 A	27-12-1994 29-03-1994 28-07-1993 08-07-1994

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.